



[www.worldracinggroup.com](http://www.worldracinggroup.com)

[www.worldofoutlaws.com](http://www.worldofoutlaws.com)

[www.dirtcar.com](http://www.dirtcar.com)

## 2019 Rule(s) Bulletin

Bulletin: 2019 – December 5, 2018

### **Section 3.0 – Personal Safety Equipment – ALL CARS, ALL DIVISIONS**

#### **3.8 - Fire Suppression**

Required for Late Models, Super DIRTcar Series, Big Block Modifieds, and 358 Modifieds in 2019. It is recommended for all other divisions.

\*\*\* Note for DIRTcar Northeast Sportsman and DIRTcar Pro Stocks, the rule will be MANDATORY for 2020. If you install the system before 2020, you will be given a 50 lb. weight break. Weights will be as follows:

Pro Stocks – 3050 lbs. without Fire Suppression. - 3000 lbs. with Fire Suppression

Sportsman – Aluminum Wheels 2450 lbs. without Fire Suppression. – 2400 lbs. with Fire Suppression

Steel Wheels 2400 lbs. without Fire Suppression – 2350 lbs. with Fire Suppression

**NOTE for Albany-Saratoga Sportsman ONLY: we will be using the weights in our rule book. These DIRTcar weight breaks do not apply to you in 2019.**

- A. All racecars shall be equipped with a thermally deployed automatic fire suppression system. The fire suppression system will consist of a DOT approved cylinder manufactured from aluminum or steel with a capacity of ten (10) lbs. of fire extinguishing agent, steel or steel reinforced lines, and two (2) thermally activated discharge nozzles.
- B. All systems must meet or exceed SFI 17.1 specifications.
- C. Systems must be fully charged with ten (10) lbs. of DuPont FE-36, 3M NOVEC 1230, or Fire Aide and display a legible and valid SFI and manufacturer label depicting fire extinguishing agent, capacity, and certification date. Cylinders that are beyond useful certification date must be inspected, serviced and re-labeled by the manufacturer.
- D. Cylinders must be mounted forward of the fuel cell. Cylinders must be securely mounted to the frame/roll cage assembly. The certification label must be unobstructed and easily accessible for inspection when the mounting is complete.
- E. The cylinder must be connected to the nozzles with steel or steel reinforced lines.
- F. Two (2) thermally activated nozzles must be used. One (1) nozzle must be located directly above the fuel cell in the fuel cell area and the second nozzle located in the driver cockpit area.
- G. An optional manual override cable is recommended.

**Dean Reynolds**  
**DIRTcar NE Series Director**

**Mark Hitchcock**  
**DIRTcar NE Technical Director**

